## **BMC**

## PROCITY 10.7 M DIESEL CITY BUS SERIES LOW FLOOR





**ENGINE** 

BRAND / MODEL

Cummins B6.7 E6

TYPF

Turbocharged Intercooler, Diesel

NUMBER OF CYLINDERS

6

**ENGINE DISPLACEMENT** 

6,7 lt

MAXIMUM POWER

204 kW (280 HP) @ 2100 rpm

MAXIMUM TORQUE

1082 Nm @ 1400 rpm

**FUEL SYSTEM** 

**FUEL TANK CAPACITY** 

328 lt

AD BLUE TANK CAPACITY

40 L

**TRANSMISSION** 

BRAND

ZF Ecolife 2 Auto

NUMBER OF GEARS

6 Forward, 1 Reverse

**AXLES** 

FRONT AXLE

Brand

ZF (Independent)

**Load Capacity** 

8200 kg

**REAR AXLE** 

Differential Brand / Model

ZF Independent

**Gear Ratio** 

3.36:0,587

Load Capacity

13000 kg

SUSPENSION

FRONT AXLE

Air Bellows (2), Hydraulic Absorbers (2)

REAR AXLE

Air Bellows (4), Hydraulic Absorbers (4)

KNEELING

Side Kneeling (ECAS)

**VEHICLE BODY** 

**BODY AND CONSTRUCTION** 

Monocoque Chassis and Body (Low-Floor)

SIZE / UNITS

275 / 70R 22,5

**RIMS** 

SIZE

8,25 x 22,5

**ELECTRICAL SYSTEM** 

**EQUIPMENT** 

24 V Negative

**BATTERIES** 

2 x 12 V / 240 Ah

**ALTERNATOR** 

24 V / 2 x 120 Ah

STEERING SYSTEM

**TYPF** 

Hvdraulic

**BRAKE SYSTEMS** 

**BRAKE SYSTEM TYPE** 

Air Controlled Disc (Front and Rear)

EBS (ABS+ASR)

**AUXILIRY BRAKE** 

Hydraulic Retarder (intarder)

Activated via Hand Lever and/or Brake Pedal

STANDARD EQUIPMENTS

Isolated Driver's Cabin (VDV Compatibility)

Adjustable Steering Integrated with Cluster

Manual Folding Disabled Ramp

Electrically Controlled Heated Side Mirrors

Air Conditioner (Cooling)

Defroster (Heating)

ECAS (Electronically Controlled Air Suspension)

Central Test Points (Front/Rear)

Sliding Side Windows

Sunvisor

Roof Hatch (x2)

Hydrostatic Fan Cooling System

Automatic Fire Detection & Extinguishing System

USB Charger (Driver's Cabin)

Digital Clock

**LED Interior Lighting** 

Fog Lights

LED Destination Boards

Tyre Pressure Monitoring System (TPMS)

**OPTIONAL EQUIPMENTS** 

**GSR II Compatibility** 

Coach Type Side Mirrors

Air Conditioner (Cooling/Heating)

Defroster (Heating/Cooling)

Preheater

**ESC** 

Heated Windscreen

Turbo Air Ventilation

Automatic Axle Greasing System

Electrically Controlled Roof Hatch

Optional Door Configuration (2-2-0)

Engine Lubrication System

LCD Monitor

Camera Surveillance and Recording System

Announcement System (Amplificator, Speakers)

Microphone

LED Destination Panels


Passenger Counting System

GPS, Wi-Fi

Park Sensor

Optional Engine Power:

182 kW (250 HP) @ 2100 rpm







## DIMENSIONS (mm)

A: Wheelbase	4470	G: Rear Overhang	3400
B: Overall Length	10710	H: Front Track Width	2096
C: Overall Width	2550	J: Rear Track Width	1832
D: Maximum Height	3100	K: Entrance Height	340
E: Inner Height	2370	L: Inner Width	2410
F: Front Overhang	2840		



Passenger Capacity 23 Seated + 73 Standing

25 Seated (23 + 2 Folding) + 67 Standing

25 Seated (23 + 2 Folding) + 60 Standing + 1 Disabled

Gross Vehicle Weight 18000 kg

BMC reserves the right to change the technical specifications of the products without prior notice (May 2025)



