

PROCITY

PROCITY 12 M DIESEL CITY BUS SERIES LOW FLOOR



BMC

ENGINE

BRAND / MODEL

Cummins B6.7 E6

TYPE

Turbocharged Intercooler, Diesel

NUMBER OF CYLINDERS

6

ENGINE DISPLACEMENT

6700 cm³

MAXIMUM POWER

204 kW @ 2100 rpm

MAXIMUM TORQUE

1082 Nm @ 1400 rpm

FUEL SYSTEM

FUEL TANK CAPACITY

235 L

AD BLUE TANK CAPACITY

38 L

TRANSMISSION

BRAND

ZF, Automatic

NUMBER OF GEARS

6 Forward, 1 Reverse

AXLES

FRONT AXLE

Brand

ZF, Rigid

Load Capacity

8200 kg

REAR AXLE

Brand

ZF [Portal]

Gear Ratio

6.20:1

Load Capacity

13000 kg

SUSPENSION

FRONT AXLE

Air Bellows (2), Hydraulic Absorbers (2)

REAR AXLE

Air Bellows (4), Hydraulic Absorbers (4)

KNEELING

Side Kneeling (ECAS)

VEHICLE BODY

BODY AND CONSTRUCTION

Monocoque Chassis and Body (Low-Floor)

TIRES

SIZE / UNITS

275 / 70R 22,5 - 6

RIMS

SIZE

8.25 x 22.5

ELECTRICAL SYSTEM

EQUIPMENT

24 V Negative

BATTERIES

2 x 12 V / 240 Ah

ALTERNATOR

24 V / 2 x 120 Ah

STEERING SYSTEM

TYPE

Hydraulic

BRAKE SYSTEMS

BRAKE SYSTEM TYPE

Air Controlled Disc (Front and Rear)

EBS (ABS+ASR)

AUXILIARY BRAKE

Hydraulic Retarder (intarder)

Activated via Hand Lever and/or Brake Pedal

STANDARD EQUIPMENTS

Air Conditioner

Manuel Foldable Disabled Ramp

Automatic Fire Extinguishing System

Electrically Controlled Heated Side Mirrors

LED Interior Lighting

LED Destination Panels

Isolated Driver Cabin

Digital Clock

Adjustable Steering Entegrated with Cluster (DWP)

OPTIONAL EQUIPMENTS

A/C with Heating Function

Automatic Greasing System

Electrically Controlled Roof Hatch

LCD Monitor

Camera Surveillance and Recording System

Automatic Oil Filling

Driver A/C (Defroster with cooling function)

Preheater

USB Charger

Tyre Pressure Monitoring System (TPMS)

Passenger Counting System

Announcement System

Rear View Camera and Display Screens

Tachograph

ESC (ESP)

Electric Fan for Ventilation

Optional Doors Configuration (2-2-0)

Double Glazed Side Glasses

Front Fog Lamps

Independent Front Axle

Optional Engine Power: 300 HP

START / STOP Engine Function



DIMENSIONS (mm)

A: Wheelbase	5850	G: Rear Overhang	3280
B: Overall Length	11970	H: Front Track Width	2096
C: Overall Width	2550	J: Rear Track Width	1832
D: Maximum Height	3100	K: Entrance Height	340
E: Inner Height	2370	L: Inner Width	2410
F: Front Overhang	2840		



CAPACITY

Passenger Capacity 26 Seating + 78 Standing

All visuals, dimensions, characteristics and equipment are for information purposes only and they are not contractual. BMC reserves the right to modify, revise or withdraw any information without prior notice (May 2022).

BMC OTOMOTİV SANAYİ VE TİCARET A.Ş.



Factory, Production and Marketing Kemalpaşa Caddesi No:288 Pınarbaşı 35060 Bornova / İzmir / TURKEY



+90 444 9 262



bmc.com.tr